


# for fixing tiles and stones.

Presenting Weber tile and stone adhesives.









weberset classic is a polymer modified cementitious tile adhesive used for fixing vitrified tiles on the floor, ceramic tiles on wall and floor of regular size, over old tiles and other flooring materials. For Internal floor and wall areas, superior bond strength for fixing tiles.

#### Features

• Tile on tile application • High adhesion strength • Longer open time with slip-resistant properties . Good workability for easy and fast application • Single component product, add only water.

#### **Recommended Substrates**

Cementitious screed, plaster, concrete masonry, blocks, and tile on tile on ceramic tiles in internal areas. For more details, refer technical data sheet, or consult Weber technical services.



Θ webe

Coverage For a **3 mm** bed thickness the coverage will be 4-4.5 kg/sqm.

Note: The coverage will vary depending on surface undulations.

#### Pack Size: 20 kg & 40 kg







weberset premier is a polymer modified cementitious tile adhesive used for fixing ceramic tiles of regular size on the wall and floor and porous natural stone on the floor. For Internal floor and wall areas, for fixing tiles.

#### Features

• Premixed material, add only water • Smooth paste consistency for easy application • Longer pot life, enable to mix a large quantity of material • Good bond strength • Economical grade adhesive.

#### **Recommended Substrates**

Cementatious screed and plasters in internal areas. For more details, refer technical data sheet, or consult Weber Technical services.

#### Coverage

For a 3 mm bed thickness the coverage will be 4-4.5 kg/sqm.

Note: The coverage will vary depending on surface undulations.

Pack Size: 20 kg & 40 kg







Adhesive for Natural stone flooring weberset nova Greu

weberset nova is a polymer modified cementitious tile adhesive used for fixing vitrified tiles, ceramic tiles, and stones of regular size on the floor with regular traffic. It is applicable for the internal and external floor for stones, high bond strength.

#### Features

White

• Fixing on tile on RCC surface without hacking • High bond strength • Premixed material, add only water • Creamy paste consistency for easy and fast application • Slip resistance for fixing tile on vertical application.

#### **Recommended Substrates**

Cementitious screed, plaster, concrete masonry, blocks, RCC, self levelling screeds, and tile on tile on tile and stone. For more details, refer technical data sheet, or consult Weber technical services.



For a 3 mm bed thickness the coverage will be 4-5 kg/sqm.

Note: The coverage will vary depending on surface undulations. Pack Size: 20 kg & 40 kg











Adhesive for Window framing, tile cladding, Natural stone flooring weberset plus-white

O White

weberset plus-white is a polymer modified cementitious tile adhesive used for fixing vitrified tiles and natural stones on wall and floor, for internal as well as external areas. It has been specially modified to give high bond with natural stone, even when used at high bed thickness, making it appropriate to be used on window sills/jams.

#### Features

• Easy to apply • High bonding strength • Can be used at higher bed thickness • Premixed material, add only water

• Slip-resistant for vertical application.

#### **Recommended Substrates**


Cementitious screed, plaster, concrete masonry, blocks, and tile on tile on ceramic tiles, in internal areas. For more details, refer technical data sheet, or consult Weber technical services.



#### Coverage

For a 3 mm bed thickness the coverage will be 4-4.5 kg/sqm.

Note: The coverage will vary depending on surface undulations. Pack Size: 20 kg





#### Adhesive for **Natural Stones** cladding weberset firm Grey White

weberset firm is a polymer modified cementitious tile adhesive used for fixing all types of tiles and natural stones like marble, granite on the wall and floor. For Internal and external floor and wall areas, suitable for marble, granite, low porosity tiles and stones.

#### Features

• For light and dark colored natural stones • Excellent workability for easy and fast application • Superior adhesion strength

• Premixed material, just add water • Longer open time.

#### **Recommended Substrates**

Cementitious screed, plaster, concrete masonry, blocks, RCC, self-leveling screeds, cementitious waterproofing, gypsum plaster, and tile-on-tile on tile and stone. For more details, refer technical datasheet, or consult Weber technical services.

#### For a 3 mm bed thickness the coverage will be 4-4.5 kg/sqm.

Note: The coverage will vary depending on surface undulations.

#### Pack Size: 20 kg

Coverage







### Adhesive for Glass Mosaics weberset glass mosaic O White

weberset glass mosaic is a polymer modified cementitious tile adhesive especially used for fixing glass mosaic, internal and external floor, and wall areas, High bond strength for glass mosaic, low porosity tiles and stones.

#### Features

 Specially designed adhesive for application in submerged conditions Excellent adhesion properties • Easy to apply • Premixed product, add only water • Extra white slip-resistance with the longer pot life **Recommended Substrates** 

Especially recommended for glass mosaic and stones due to its white color which adds color and aesthetic look. Recommended for application on cementitious substrates and self-leveling screeds, blocks and suitable under wet and dry conditions including swimming pools and fountains. For more details, refer technical data

sheet, or consult Weber technical service.

#### Coverage

For a 2 mm bed thickness the coverage will be 2-2.5 kg/sqm.

Note: The coverage will vary depending on surface undulations.

Pack Size: 20 kg







weberset flex is a polymer modified cementitious tile adhesive used for fixing tiles and natural stones of large format on wall and floor where nominal substrate movement is expected. For Internal and external floor and wall areas, for fixing tiles and stone on areas of structural movements.

#### Features

• Fixing on the tile on RCC surface without hacking • High bond strength • Premixed material, add only water • Creamy paste consistency for easy and fast application • Slip resistance for fixing tile on vertical application.

#### **Recommended Substrates**

Substrates subjected to moderate vibration, including cementitious screed, plaster, concrete masonry, blocks, RCC, self-levelling screeds, cementitious waterproofing, gypsum plaster, and tile-on-tile on tile and stone. For more details, refer technical data sheet, or consult Weber technical services.





For a **3 mm** bed thickness the coverage will be 4-5 kg/sqm.

Note: The coverage will vary depending on surface undulations. Pack Size: 20 kg



(←











### Adhesive for artificial stone cladding weberset ultra

O White

weberset ultra is a two component high performance modified adhesive used for fixing impregnated stone, tile and large format tile and stones where nominal to moderate substrate movement is expected. For Internal and external floor and wall areas, for fixing natural composite tiles. and impregnated stones.

#### Features

• Especially suited for fixing impregnated stone and composite marble • Two component product • Highly flexible, to withstand medium substrate movement • Ultimate adhesion strength • Longer workability for easy and faster application.

#### **Recommended Substrates**

Substrates subjected to moderate vibration, including cementitious screed, plaster, concrete masonry, blocks, RCC, self-leveling screeds, cementitious waterproofing, gypsum plaster, and tile-on-tile on tile and stone. For more details, refer technical data sheet, or consult Weber technical services.

#### Coverage

For a **3 mm** bed thickness the coverage for Single spreading will be 4 - 4.5 kg/sqm.

Double spreading 6 kg/sqm.

Note : The coverage will vary depending on surface undulations. Pack Size: 16 kg + 5 L liquid



#### Adhesive for tile and stone on metal and glass surface weber epoxy

adhesive

weber epoxy adhesive is a three component, heavy duty, chemical resistant adhesive for fixing tile and stone of small and big format on wall and floor. It provides excellent, high durable bond strength for fixing tile & stone on metal surfaces. Weber epoxy adhesive is used in wet, internal and external areas.

#### Features

• Excellent adhesion on metal surfaces • Highly durable • Internal and external application . For tile & stone fixing on elevated structures.

#### **Recommended Substrates**

On metal, MS sheets, aluminum panel, RCC, self-leveling screed, acrylic sheet, metal ACP sheets, fibre-cement, gypsum board and plywood. For more details, refer technical data sheet, or consult Weber technical services.

#### Coverage

For 3 mm bed thickness the coverage will be 5-6 kg/sqm Note: The coverage will vary depending on surface undulations.

Pack Size: 6 kg weber bond poxy (resin-hardner kit)

18 kg weber bond poxyfill (epoxy adhesive filler)





#### Adhesive for large format stone on drywall and plywood

weberfix drywall

weberfix drywall is a 2 component high-performance tile and stone adhesive, used for almost all types of tiles, nearly all types of substrates including green and moisture sensitive marble and agglomerates. Weberfix drywall is specially formulated, for fixing large format tiles and stones on drywall and plywood.

#### Features

• Moisture free system • Very high bond strength • 2 Component adhesive • Fast setting.

#### **Recommended Substrates**

For fixing large format tiles and stones on cementitious substrates, all types of drywall like boards or plywood. For more details, refer technical data sheet, or consult Weber technical services.

#### Coverage

For every mm bed thickness the coverage will be 1.62 kg/sqm Note: The coverage may vary depending on surface undulations & other site conditions

Pack Size: 20 kg (Component A : 15 kg Bucket Component B : 5 kg Bucket) 5 kg (Component A : 3.75 kg & Component B: 1.25 kg inside bucket)





## Application tools



weber

tile

spacer

6mm x 6mm notched trowel suitable for 3mm bed thickness.

#### Features

- Special high wear resistance.
- Ergonomic handle for ease of use.
- Perfect flatness of the plate.

• Improves adherence of the mortar on to work surface.

Spacers for obtaining a perfect finish in any tile and stone installation work.

#### Features

- For perfect spaces in between tiles
- Quality base material, without impurities or imperfections.
- Suitable for all types of tiles and stones.

## Tile and Stone Care

**Under-tile** impregnator for stones prone to discoloration webersys stoneprotect

weber stone protect is a penetrating sealer that protects the interior of extra porous stones such as fine-grained granites, marble, limestone, slate, and sandstone. It can also provide repellency for concrete and grouts. This below surface sealer is recommended for sealing stones for both interior and exterior.

#### Features

- Water-based formula eliminates any chances of fire
- Ready to use product
- Simple to apply and user-friendly
- Helps adhesion and prevents penetration of fluids and dirt
- Safe on food handling surface.

#### **Technical Parameters#**

Specific gravity	1.02+/-0.01
ρΗ	7-9
Colour	Milky white
Viscosity	B4 cup 12-16 sec

#### Consumption

12-20 sqm/litre for double coat. Consumption may vary depending on surface conditions and porosity material.

Pack Size: 20 Lit Drum & 1 Lit Bottle





aquaseal

weber aquaseal is a polymer based sealer designed for the protection of natural & synthetic stone. The unique formulation gives an excellent water repellent as well as oleophobic, i.e. oil repellent properties. It exhibits high resistance to oil and water stain on the surface treated with weber aquaseal. The treated pores of the surface form an invisible barrier allowing the vapour.

#### Features

- It can be used as a multipurpose additive for enhancing the performance of concrete / mortar mix.
- It can be used for internal as well as external applications. Non toxic, suitable for use in potable water.
- It improves the workability of mixes.
- It makes the structure impermeable to liquids.
- Waterproof layer subjected to foot traffic, needs screed protection.

#### Technical Parameters#

Appearance	Clear liquid
Density	1.02 + 0.02 gm/cc
оН	7-9

#### Consumption

Consumption: 3sqm – 35 sqm/lit,consumption may vary depending on the porosity level of the surface.

Pack Size: 20 Lit Drum, 5 Lit & 1 Lit Bottle





Solvent based impregnating sealer for tiles and stones

webersys stoneseal

weber stoneseal is a polymer-based solvent sealer designed for the protection of natural and synthetic stone. The unique formulation gives an excellent water repellent as well as oleophobic, i.e. oil repellent properties. It exhibits high resistance to oil and water stain on the surface treated with weber stoneseal. The treated pores of the surface form an invisible barrier allowing the vapor.

#### Features

- Used for even low porous stone and marble
- Easy to apply using brush, sponge or cloth
- Can be applied for both external and internal application
- Highly durable and economical
- Ready to use no dilution required at site
- Superior coverage
- Seal and protect against stain of eatables.

#### **Technical Parameters#** Appearance

Density at 25 deg cent

#### Consumption

Consumption: 3sqm – 30 sqm / lit, consumption may vary depending on the porosity level of the surface.

Light Yellowish

0.86 +/- 0.02 gm/cc

#### Pack Size: 20 Lit Drum & 1 Lit Bottle





#### Heavy duty tile cleaner for tough stains

weberklin ceraplus

weberklin ceraplus is a specially formulated ceramic surface cleaner and tough cement stain remover. It can be used on all types of ceramic material and can remove salt buildups due to stagnant water / continuous exposure to water with ease.

#### Features

- Easily removes even tough cement stains.
- No etching of ceramic products.
- Does not effect the glaze of tiles.
- Economical in use
- Removes all residual substances, like soap, scum deposit, mineral and salt deposits easily.
- When used before grouting tile joints, provides contamination free grout, with longer life and better color performance.

#### **Technical Information**

Colour	Blue
Specific Gravity	1.05 @ 27°C
Soaking time	3-5 mins

#### Pack Size: 1 Lit Bottle






#### Tile adhesive - Directions for use



Clean the substrate of oil stains and bond inhibiting compounds. Also remove any loose particles dirt, dust, and laitance.



Ensure that the surface is flat (hard and rigid) for the given application.



Ensure that the surface is well saturated before application in the case of cementatious substrates.



Mix as per mixing ratio defined in datasheet.



For cementatious adhesive always add powder to water.



After mixing allow the paste to stand for 2 min for it to mature.



Do not attempt to extend the more water to the mix.




Apply adhesive over the surface using the straight edge of the notched trowel If the adhesive is buttered to the tile, then ensure proper coverage of tile surface to avoid voids



use weber tile spacer for recommended spacing between the tiles.



After 24 hours grouting can be done on tiles and stones.







TILE & STONE CARE



https://goo.gl/d39avs

**TILE & STONE FIXING** 

in.weber/complete-tile-

and-stone-fixing-solution

complete tile and stone

code

for

QR

care solutions

Scan

Scan QR code to download android app for product information and technical data for our complete product range, directly from your smartphone.



#### Saint-Gobain India Pvt. Ltd. - Weber business,

Corporate Office: 5th level, Leela Business Park, Andheri-Kurla Road, Andheri East, Mumbai – 400059 India. Email: weber-india@saint-gobain.com





/SaintGobainWeberIndia



lin



/company/saint-gobain-weber-india

/SaintGobainWeberIndia

